

# Seat Numbers



## SQUARE – with rounded corners

Black text with glowing background

1 1/8" square (31.9mm)

## DISC

Black text with glowing background

1 9/16" round (40mm)



## ELIPSE

Black text with glowing background

1 1/4" x 2 1/8" (18.7mm x 56.7mm)



**Also available as OBROUND** – 9/16" x 1 1/16" (14.7mm x 27.2mm) or 5/8" x 1 1/8" (16mm x 44.6mm)  
Please contact us for pricing on custom shapes and sizes.

**ecoglo® seat numbers** guide your customers to their seats. Working equally well in light and dark conditions, they reduce the disruption of people movements to other customers, increase the efficiency of ushers, and make it easier for a customer to go to the concessions or other facilities.

The **ecoglo®** seat number is designed to be visible for the length of a performance (concert, theatre, movies, etc) to enhance the orderly movement of people to and from their seats. Directional instructions or icons can be installed to provide more efficient egress.

**Benefits and Technical Details** Ecoglo Seat Numbers meet or exceed the performance criteria specified in the following tests or standards:

1. **High Visibility in Dark or Light conditions.**

*Brightness:*

ASTM E2072-04, Standard Specification for Photoluminescent (Phosphorescent) Safety Markings.

ASTM E2073-02, Standard Test Method for Photopic Luminance of Photoluminescent (Phosphorescent) Markings.

DIN 67510 Part 1, Phosphorescent Pigments and Products: Measurement and identification by the manufacturer.

ISO 17398:2004 Clause 7.11, Safety Colours and Safety Signs- Classification, Performance and Durability of Safety Signs.

2. **High Durability Indoors and Outdoors.**

*UV Stability:* ASTM G155-04 Cycle 1 2000hrs, Standard Practice for Operating Xenon Arc Light Apparatus for Exposure of Nonmetallic Materials.

*Salt Spray Resistance:* ASTM B117-97 500hrs, Standard Practice for Operating Salt Spray (Fog) Apparatus.

*Freeze-Thaw Resistance:* ASTM C1026-87(1996), Standard Test Method for Measuring the Resistance of Ceramic Tile to Freeze-Thaw Cycling.

3. **Easy Cleaning.**

*Washability:*

ASTM D4828-94(2003), Standard Test Methods for Practical Washability of Organic Coatings.

4. **No Radioactivity or Toxicity.**

*Radioactivity:* ASTM D3648-2004, Standard Practices for the Measurement of Radioactivity.

*Toxicity:* Bombardier SMP 800-C (2000), Toxic Gas Generation Test.

5. **Does not burn.**

*Flammability:*

ASTM E162-02, Standard Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source.

ASTM D635-03, Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position.

FAA AC 23.2 Paragraph 4.b, Horizontal Burn Test.